

Page 1 of 8  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)  
 Revision date / version: 25.11.2024 / 0002  
 Replacing version dated / version: 13.09.2023 / 0001  
 Valid from: 25.11.2024  
 PDF print date: 28.11.2024  
 KNAPP PU+ KLEBER FASERVERSTÄRKT

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**KNAPP PU+ KLEBER FASERVERSTÄRKT**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Adhesive

**Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

Knapp GmbH  
 Wassergasse 31  
 3324 Euratsfeld  
 Tel: +43 (0)7474 / 799 10  
 Fax: +43 (0)7474 / 799 10 99  
 mholzer@knapp-verbinder.com

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

---

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (WIC)  
 +1 872 5888271 (WIC)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) 1272/2008 (CLP)**

Hazard class	Hazard category	Hazard statement
Eye Irrit.	2	H319-Causes serious eye irritation.
STOT SE	3	H335-May cause respiratory irritation.
Skin Irrit.	2	H315-Causes skin irritation.
Resp. Sens.	1	H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens.	1	H317-May cause an allergic skin reaction.
Carc.	2	H351-Suspected of causing cancer.
STOT RE	2	H373-May cause damage to organs through prolonged or repeated exposure by inhalation (respiratory system).

#### 2.2 Label elements

**Labeling according to Regulation (EC) 1272/2008 (CLP)**



**Danger**

H319-Causes serious eye irritation. H335-May cause respiratory irritation. H315-Causes skin irritation. H334-May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317-May cause an allergic skin reaction. H351-Suspected of causing cancer. H373-May cause damage to organs through prolonged or repeated exposure by inhalation (respiratory system).

P201-Obtain special instructions before use. P260-Do not breathe vapours or spray. P280-Wear protective gloves / protective clothing / eye protection / face protection. P284-Wear respiratory protection.

P302+P352-IF ON SKIN: Wash with plenty of water / soap. P304+P340-IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313-IF exposed or concerned: Get medical advice / attention.

EUH204-Contains isocyanates. May produce an allergic reaction.

As from 24 August 2023 adequate training is required before industrial or professional use.

4,4'-methylenediphenyl diisocyanate  
 Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate  
 Methylenediphenyl diisocyanate, modified

#### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).  
 The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

n.a.

#### 3.2 Mixtures

Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	
Registration number (REACH)	01-2119457015-45-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	905-806-4
CAS	---
content %	5-<25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Resp. Sens. 1, H334 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 (respiratory system) (as inhalation)
Specific Concentration Limits and ATE	Skin Irrit. 2, H315: >=5 % Eye Irrit. 2, H319: >=5 % Resp. Sens. 1, H334: >=0,1 % STOT SE 3, H335: >=5 % ATE (as inhalation, Dusts or mist): 1,5 mg/l/4h ATE (as inhalation, Vapours): 11 mg/l/4h

Methylenediphenyl diisocyanate, modified	
Registration number (REACH)	01-2119457013-49-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	500-040-3
CAS	25686-28-6
content %	5-<25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Resp. Sens. 1, H334 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 (respiratory system) (as inhalation)
Specific Concentration Limits and ATE	Skin Irrit. 2, H315: >=5 % Eye Irrit. 2, H319: >=5 % Resp. Sens. 1, H334: >=0,1 % STOT SE 3, H335: >=5 % ATE (as inhalation, Dusts or mist): 1,5 mg/l/4h ATE (as inhalation, Vapours): 11 mg/l/4h

4,4'-methylenediphenyl diisocyanate	
Registration number (REACH)	01-2119457014-47-XXXX
Index	615-005-00-9
EINECS, ELINCS, NLP, REACH-IT List-No.	202-966-0
CAS	101-68-8
content %	5-<25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Resp. Sens. 1, H334 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 (respiratory system) (as inhalation)
Specific Concentration Limits and ATE	Skin Irrit. 2, H315: >=5 % Eye Irrit. 2, H319: >=5 % Resp. Sens. 1, H334: >=0,1 % STOT SE 3, H335: >=5 % ATE (as inhalation, Aerosol): 1,5 mg/l/4h ATE (as inhalation, Vapours): 11 mg/l/4h

Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-hydro- .omega.-hydroxy-	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	---
CAS	25322-69-4
content %	1-10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302

4-Hydroxybutyric acid lactone	
Registration number (REACH)	01-2119471839-21-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	202-509-5
CAS	96-48-0
content %	1-<3
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302 Eye Dam. 1, H318 STOT SE 3, H336
Specific Concentration Limits and ATE	ATE (oral): 1582 mg/kg

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
 The substances named in this section are given with their actual, appropriate classification!  
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.  
 The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

##### Inhalation

Remove person from danger area.

Page 2 of 8  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)  
 Revision date / version: 25.11.2024 / 0002  
 Replacing version dated / version: 13.09.2023 / 0001  
 Valid from: 25.11.2024  
 PDF print date: 28.11.2024  
 KNAPP PU+ KLEBER FASERVERSTÄRKT

Supply person with fresh air and consult doctor according to symptoms.  
 If the person is unconscious, place in a stable side position and consult a doctor.  
 Respiratory arrest - Artificial respiration apparatus necessary.

#### Skin contact

Wipe off residual product carefully with a soft, dry cloth.  
 Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.  
 Dab away with polyethylene glycol 400

#### Eye contact

Remove contact lenses.  
 Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

#### Ingestion

Rinse the mouth thoroughly with water.  
 Do not induce vomiting - give copious water to drink. Consult doctor immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. The following may occur:

- Dermatitis (skin inflammation)
- Drying of the skin.
- Allergic contact eczema
- Discoloration of the skin
- Irritant to mucosa of the nose and throat
- Coughing
- Headaches
- Effect on the central nervous system
- Asthmatic symptoms
- In case of sensitivity, concentrations below the limit value may already result in asthmatic symptoms.
- Respiratory distress
- In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

#### 4.3 Indication of any immediate medical attention and special treatment needed

In case of irritation of the lungs, perform first-aid with controlled-dosage aerosol dexamethasone.  
 Pulmonary oedema prophylaxis  
 Medical supervision necessary due to possibility of delayed reaction.

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

##### Suitable extinguishing media

- CO2
- Extinction powder
- Water jet spray
- Foam

##### Unsuitable extinguishing media

High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

- Oxides of carbon
- Oxides of nitrogen
- Isocyanates
- Hydrocyanic acid (hydrogen cyanide)
- Toxic gases
- Danger of bursting (explosion) when heated

#### 5.3 Advice for firefighters

For personal protective equipment see Section 8.  
 In case of fire and/or explosion do not breathe fumes.  
 Protective respirator with independent air supply.  
 According to size of fire  
 Full protection, if necessary.  
 Cool container at risk with water.  
 Dispose of contaminated extinction water according to official regulations.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

##### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.  
 Ensure sufficient ventilation, remove sources of ignition.  
 Avoid dust formation with solid or powder products.  
 Leave the danger zone if possible, use existing emergency plans if necessary.  
 Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

##### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

#### 6.2 Environmental precautions

If leakage occurs, dam up.  
 Resolve leaks if this possible without risk.  
 Prevent surface and ground-water infiltration, as well as ground penetration.  
 Prevent from entering drainage system.  
 If accidental entry into drainage system occurs, inform responsible authorities.

#### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

Allow to stand for a few days in an unclosed container until reaction no longer occurs.

Keep moist.

Do not close packing drum.

CO2 formation in closed tanks causes pressure to rise.

#### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

### SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

#### 7.1 Precautions for safe handling

##### 7.1.1 General recommendations

Ensure good ventilation.  
 Avoid inhalation of the vapours.  
 If applicable, suction measures at the workstation or on the processing machine necessary.  
 Avoid contact with eyes or skin.  
 No contact with products of this type in case of allergies, asthma und chronic respiratory tract disorders.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Keep protected from direct sunlight and temperatures over 50°C.

Only store at temperatures from 15°C to 25°C.

Store in a dry place.

#### 7.3 Specific end use(s)

Adhesive

Observe the instructions for good working practice and the recommendations for risk assessment.

Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries,

depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

Observe special requirements for isocyanates, also within the framework of the risk assessment and definition of protective measures.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Chemical Name	Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate	
WEL-TWA: 0,02 mg/m3 (Isocyanates, all (as -NCO)) (WEL-TWA), 10 µg/m3 (until 31.12.2028), 6 µg/m3 (from 01.01.2029) (measured as NCO, diisocyanates) (EU)	WEL-STEL: 0,07 mg/m3 (Isocyanates, all (as -NCO)) (WEL-STEL)	---
Monitoring procedures: ---		
BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the end of the period of exposure) (BMGV)	Other information: Sen (Isocyanates, all) (WEL) / (13), (15) (diisocyanates) (EU)	

Chemical Name	Methylenediphenyl diisocyanate, modified	
WEL-TWA: 0,02 mg/m3 (Isocyanates, all (as -NCO)) (WEL-TWA), 10 µg/m3 (until 31.12.2028), 6 µg/m3 (from 01.01.2029) (measured as NCO, diisocyanates) (EU)	WEL-STEL: 0,07 mg/m3 (Isocyanates, all (as -NCO)) (WEL-STEL)	---
Monitoring procedures: ISO 16702 (Workplace air quality – determination of total isocyanate groups in air using 2-(1-methoxyphenyl)piperazine and liquid chromatography) - 2007 MDHS 25/4 (Organic isocyanates in air – Laboratory method using sampling either onto 2-(1-methoxyphenyl)piperazine coated glass fibre filters followed by solvent desorption or into impingers and analysis using high performance liquid chromatography) - 2015		
BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the end of the period of exposure) (BMGV)	Other information: (13), (15) (diisocyanates) (EU)	

Chemical Name	4,4'-methylenediphenyl diisocyanate	
WEL-TWA: 0,02 mg/m3 (Isocyanates, all (as -NCO)) (WEL-TWA), 10 µg/m3 (until 31.12.2028), 6 µg/m3 (from 01.01.2029) (measured as NCO, diisocyanates) (EU)	WEL-STEL: 0,07 mg/m3 (Isocyanates, all (as -NCO)) (WEL-STEL)	---
Monitoring procedures: ISO 16702 (Workplace air quality – determination of total isocyanate groups in air using 2-(1-methoxyphenyl)piperazine and liquid chromatography) - 2007 MDHS 25/4 (Organic isocyanates in air – Laboratory method using sampling either onto 2-(1-methoxyphenyl)piperazine coated glass fibre filters followed by solvent desorption or into impingers and analysis using high performance liquid chromatography) - 2015 - EU project BC/CEN/ENTR/000/2002-16 card 7-4 (2004) - NIOSH 5521 (ISOCYANATES, MONOMERIC) - 2003 - NIOSH 5522 (ISOCYANATES) - 1998 - NIOSH 5525 (ISOCYANATES, TOTAL (MAP)) - 2003 - OSHA 18 (Diisocyanates 2,4-TDI and MDI) - 1980 - OSHA 47 (Methylene Bisphenyl Isocyanate (MDI)) - 1984		
BMGV: 1 µmol isocyanate-derived diamine/mol creatinine in urine (At the end of the period of exposure) (BMGV)	Other information: Sen (Isocyanates, all) (WEL) / (13), (15) (diisocyanates) (EU)	

Chemical Name	Silicon dioxide	
WEL-TWA: 6 mg/m3 (total inh. dust), 2,4 mg/m3 (resp. dust)	WEL-STEL: ---	---
Monitoring procedures: ---		
BMGV: ---	Other information: ---	

Chemical Name	Glass, oxide, chemicals	
WEL-TWA: 2 fibres/ml, 5 mg/m3 (l:d >= 3:1, < 6µm) (MMMMF)	WEL-STEL: ---	---
Monitoring procedures: ---		
BMGV: ---	Other information: ---	

Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	37	µg/l	
	Environment - marine		PNEC	0,37	µg/l	
	Environment - soil		PNEC	2,33	mg/kg	
	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	3,7	µg/l	
	Environment - sediment, freshwater		PNEC	11,7	mg/kg dry weight	
	Environment - sediment, marine		PNEC	1,17	mg/kg dry weight	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,025	mg/m3	

Page 3 of 8  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)  
 Revision date / version: 25.11.2024 / 0002  
 Replacing version dated / version: 13.09.2023 / 0001  
 Valid from: 25.11.2024  
 PDF print date: 28.11.2024  
 KNAPP PU+ KLEBER FASERVERSTÄRKT

Consumer	Human - inhalation	Short term, local effects	DNEL	0,05	mg/m3
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,1	mg/m3
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,05	mg/m3

Methylenediphenyl diisocyanate, modified						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,0037	mg/l	
	Environment - marine		PNEC	0,0037	mg/l	
	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - soil		PNEC	2,33	mg/kg dry weight	
	Environment - water, sporadic (intermittent) release		PNEC	37	mg/l	
	Environment - sediment, freshwater		PNEC	11,7	mg/kg dry weight	
	Environment - sediment, marine		PNEC	1,17	mg/kg dry weight	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,025	mg/m3	
Consumer	Human - inhalation	Short term, local effects	DNEL	0,05	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,05	mg/m3	

4,4'-methylenediphenyl diisocyanate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	3,7	µg/l	
	Environment - marine		PNEC	0,37	µg/l	
	Environment - sewage treatment plant		PNEC	1	mg/l	
	Environment - soil		PNEC	2,33	mg/kg dw	
	Environment - sporadic (intermittent) release		PNEC	37	µg/l	
	Environment - sediment, freshwater		PNEC	11,7	mg/kg dry weight	
	Environment - sediment, marine		PNEC	1,17	mg/kg dry weight	
Consumer	Human - oral	Short term, systemic effects	DNEL	20	mg/kg bw/day	
Consumer	Human - dermal	Short term, local effects	DNEL	17,2	mg/cm <sup>2</sup>	
Consumer	Human - dermal	Short term, systemic effects	DNEL	25	mg/kg bw/day	
Consumer	Human - inhalation	Short term, local effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	0,05	mg/m3	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,025	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	0,025	mg/m3	
Workers / employees	Human - dermal	Short term, local effects	DNEL	28,7	mg/cm <sup>2</sup>	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	50	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	0,1	mg/m3	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	0,05	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,05	mg/m3	

4-Hydroxybutyric acid lactone						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,056	mg/l	
	Environment - marine		PNEC	0,0056	mg/l	
	Environment - sporadic (intermittent) release		PNEC	0,56	mg/l	
	Environment - sediment, freshwater		PNEC	0,24	mg/kg dw	
	Environment - sediment, marine		PNEC	0,02	mg/kg dw	
	Environment - soil		PNEC	0,014683	mg/kg dw	

	Environment - sewage treatment plant		PNEC	452	mg/l
Consumer	Human - inhalation	Long term, systemic effects	DNEL	28	mg/m3
Consumer	Human - inhalation	Short term, systemic effects	DNEL	340	mg/m3
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	958	mg/m3
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	130	mg/m3
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	19	mg/kg bw/day

Ⓒ - United Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).  
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU;  
 (8) = Inhalable fraction (2004/37/EC, 2017/164/EU), (9) = Respirable fraction (2004/37/EC, 2017/164/EU), (11) = Inhalable fraction (2004/37/EC), (12) = Inhalable fraction, Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/EC), |  
 | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).  
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU;  
 (8) = Inhalable fraction (2004/37/EC, 2017/164/EU), (9) = Respirable fraction (2004/37/EC, 2017/164/EU), (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU), |  
 | BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).  
 (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |  
 | Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU;  
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (98/24/EC, 2004/37/EC), (14) = The substance can cause sensitisation of the skin (2004/37/EC), (15) = Substantial contribution to the total body burden via dermal exposure possible. |

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction. If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here. Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

Recommended

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

>= 0,35

Permeation time (penetration time) in minutes:

>= 480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:

Colour:

Odour:

Melting point/freezing point:

Boiling point or initial boiling point and boiling range:

Flammability:

Lower explosion limit:

Upper explosion limit:

Flash point:

Auto-ignition temperature:

Paste, liquid.

Opaque

Slightly

There is no information available on this parameter.

There is no information available on this parameter.

Combustible.

There is no information available on this parameter.

There is no information available on this parameter.

There is no information available on this parameter.

n.a.

(GB) Page 4 of 8  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)  
 Revision date / version: 25.11.2024 / 0002  
 Replacing version dated / version: 13.09.2023 / 0001  
 Valid from: 25.11.2024  
 PDF print date: 28.11.2024  
 KNAPP PU+ KLEBER FASERVERSTÄRKT

Decomposition temperature: There is no information available on this parameter.  
 pH: Mixture reacts with water.  
 Kinematic viscosity: There is no information available on this parameter.  
 Solubility: Insoluble  
 Partition coefficient n-octanol/water (log value): Does not apply to mixtures.  
 Vapour pressure: There is no information available on this parameter.  
 Density and/or relative density: ~1,14 g/cm<sup>3</sup>  
 Relative vapour density: There is no information available on this parameter.  
 Particle characteristics: Does not apply to liquids.

## 9.2 Other information

Explosives: Product is not explosive.  
 Oxidising liquids: No  
 Evaporation rate: n.a.  
 Bulk density: n.a.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

reacts with water

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

Exothermic reaction possible with:

Alcohols  
 Amines  
 Bases  
 Acids  
 Water  
 Development of:  
 Carbon dioxide  
 CO<sub>2</sub> formation in closed tanks causes pressure to rise.  
 Pressure increase will result in danger of bursting.

### 10.4 Conditions to avoid

See also section 7.  
 Protect from humidity.  
 Polymerisation due to high heat is possible.  
 T > ~ 260°C

### 10.5 Incompatible materials

See also section 7.

Acids  
 Bases  
 Amines  
 Alcohols  
 Water

### 10.6 Hazardous decomposition products

See also section 5.2  
 No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

#### KNAPP PU+ KLEBER FASERVERSTÄRKT

Toxicity / effect	Endpo int	Value	Unit	Organis m	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/k g			calculated value n.d.a.
Acute toxicity, by dermal route:						
Acute toxicity, by inhalation:	ATE	>20	mg/l/ 4h			calculated value, Vapours n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

#### Reaction mass of 4,4'-methylenebisphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate

Toxicity / effect	Endpo int	Value	Unit	Organis m	Test method	Notes
Acute toxicity, by oral route:	LD50	> 10000	mg/k g	Rat		
Acute toxicity, by dermal route:	LD50	> 9400	mg/k g	Rabbit		
Acute toxicity, by inhalation:	LC50	0,49	mg/l/ 4h	Rat		Mist, Dust., Does not conform with EU classification.
Acute toxicity, by inhalation:	ATE	11	mg/l/ 4h			Vapours
Acute toxicity, by inhalation:	ATE	1,5	mg/l/ 4h			Dusts or mist Irritant
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	

Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Yes (inhalation and skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	Regulation (EC) 440/2008 B.13/B.14 (REVERSE MUTATION TEST USING BACTERIA)	Negative
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Carcinogenicity:				Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Carc. 2

#### Methylenebisphenyl diisocyanate, modified

Toxicity / effect	Endpo int	Value	Unit	Organis m	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/k g	Rat	OECD 401 (Acute Oral Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	ATE	11	mg/l/ 4h			Vapours
Acute toxicity, by inhalation:	ATE	1,5	mg/l/ 4h			Dusts or mist
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Mouse		Yes (inhalation)
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Yes (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	Regulation (EC) 440/2008 B.13/B.14 (REVERSE MUTATION TEST USING BACTERIA)	Negative
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOEC	0,23	mg/m <sup>3</sup>	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	

#### 4,4'-methylenebisphenyl diisocyanate

Toxicity / effect	Endpo int	Value	Unit	Organis m	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/k g	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>9400	mg/k g	Rabbit	OECD 402 (Acute Dermal Toxicity)	Analogous conclusion
Acute toxicity, by inhalation:	ATE	11	mg/l/ 4h			Vapours
Acute toxicity, by inhalation:	ATE	1,5	mg/l/ 4h			Aerosol
Acute toxicity, by inhalation:	LC50	0,368	mg/l/ 4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol, Does not conform with EU classification.
Acute toxicity, by inhalation:	LC50	1,5	mg/l/ 4h			Aerosol, Expert judgement.
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2, Analogous conclusion
Respiratory or skin sensitisation:				Guinea pig		Yes (inhalation)
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Skin Sens. 1
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Rat	OECD 489 (In Vivo Mammalian Alkaline Comet Assay)	Negative
Carcinogenicity:				Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Aerosol, Analogous conclusion, Carc. 2
Reproductive toxicity:	NOEL	4-12	mg/m <sup>3</sup>	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Aerosol, Analogous conclusion



Page 6 of 8  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)  
 Revision date / version: 25.11.2024 / 0002  
 Replacing version dated / version: 13.09.2023 / 0001  
 Valid from: 25.11.2024  
 PDF print date: 28.11.2024  
 KNAPP PU+ KLEBER FASERVERSTÄRKT

12.1. Toxicity to fish:	LC50	96h	> 1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	NOEC/N OEL	21d	>10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	24h	> 1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.2. Persistence and degradability:		28d	0	%	activated sludge	OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	
12.3. Bioaccumulative potential:	BCF		200				Not to be expected
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

Methylenediphenyl diisocyanate, modified							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LL50	96h	>100	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	NOEC/N OEL	21d	>=10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EL50	48h	9	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EL50	72h	>100	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	0	%	activated sludge	OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	
12.2. Persistence and degradability:		28d	0	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	
12.3. Bioaccumulative potential:	BCF	28d	200		Cyprinus caprio	OECD 305 (Bioconcentration - Flow-Through Fish Test)	
12.3. Bioaccumulative potential:	BCF		200			OECD 305 (Bioconcentration - Flow-Through Fish Test)	Not to be expected
12.4. Mobility in soil:	Log Koc		4,5				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.6. Endocrine disrupting properties:							Negative
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other organisms:	EC50	14d	>1000	mg/kg dw	Avena sativa		
Other organisms:	EC0	14d	>1000	mg/kg dw	Lactuca sativa		
Toxicity to annelids:	LC50	14d	>1000	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests)	

4,4'-methylenediphenyl diisocyanate							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	24h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to daphnia:	NOEC/N OEL	21d	>10	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Analogous conclusion
12.1. Toxicity to algae:	ErC50	72h	>1640	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	0	%		OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	Not biodegradable, With water at the interface, transforms slowly with formation of CO2 into a firm, insoluble reaction product with a high melting point (polycarbamide). According to experience available to date, polycarbamide is inert and non-degradable Analogous conclusion
12.3. Bioaccumulative potential:	Log Pow		4,51-5,22				A notable biological accumulation potential has to be expected (LogPow > 3).
12.3. Bioaccumulative potential:	BCF	28d	200		Cyprinus caprio	IUCLID Chem. Data Sheet (ESIS)	Not to be expected
12.4. Mobility in soil:	H (Henry)		0,0229	Pa·m <sup>3</sup> /mol			
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion
Other organisms:	NOEC/N OEL	14d	>1000	mg/kg	Lactuca sativa	OECD 208 (Terrestrial Plants, Growth Test)	Analogous conclusion
Other organisms:	NOEC/N OEL	14d	>1000	mg/kg	Avena sativa	OECD 208 (Terrestrial Plants, Growth Test)	Analogous conclusion
Other information:	AOX						Does not contain any organically bound halogens which can contribute to the AOX value in waste water.

Page 7 of 8  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)  
 Revision date / version: 25.11.2024 / 0002  
 Replacing version dated / version: 13.09.2023 / 0001  
 Valid from: 25.11.2024  
 PDF print date: 28.11.2024  
 KNAPP PU+ KLEBER FASERVERSTÄRKT

Other information:						According to experience available to date, polycarbamide is inert and non-degradable. With water at the interface, transforms slowly with formation of CO <sub>2</sub> into a firm, insoluble reaction product with a high melting point (polycarbamide).
Toxicity to annelids:	NOEC/N OEL	14d	> 100	mg/kg	Lumbricus terrestris	OECD 207 (Earthworm, Acute Toxicity Tests) Analogous conclusion
Toxicity to annelids:	EC50	14d	>1000	mg/kg	Eisenia foetida	OECD 207 (Earthworm, Acute Toxicity Tests) Analogous conclusion

Polyoxy(methyl-1,2-ethanediyl), -alpha.-hydro.-omega.-hydroxy-							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100		Poecilia reticulata	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC0	72h	>100	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	87	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	
12.3. Bioaccumulative potential:	Log Kow		0-1				calculated value
12.4. Mobility in soil:	Log Koc		0-1				
12.4. Mobility in soil:	Koc		1-10				
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion

4-Hydroxybutyric acid lactone							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	56	mg/l	Lepomis macrochirus	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	>500	mg/l	Daphnia magna		
12.2. Persistence and degradability:	DOC	13d	98	%			
12.2. Persistence and degradability:	BOD	14d	77	%	activated sludge	OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	Readily biodegradable
12.4. Mobility in soil:	Koc		6,477				calculated value
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Other organisms:	EC50		4518	mg/l	Tetrahyman pyriformis		

Silicon dioxide							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes

12.2. Persistence and degradability:							Inorganic products cannot be eliminated from water through biological purification methods.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Glass, oxide, chemicals							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

## SECTION 13: Disposal considerations

**13.1 Waste treatment methods**  
**For the substance / mixture / residual amounts**  
 EC disposal code no.:  
 The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)  
 08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances  
 08 05 01 waste isocyanates  
 Recommendation:  
 Sewage disposal shall be discouraged.  
 Pay attention to local and national official regulations.  
 E.g. suitable incineration plant.  
 Hardened product:  
 E.g. dispose at suitable refuse site.  
**For contaminated packing material**  
 Pay attention to local and national official regulations.  
 Empty container completely.  
 Uncontaminated packaging can be recycled.  
 Dispose of packaging that cannot be cleaned in the same manner as the substance.  
 15 01 10 packaging containing residues of or contaminated by hazardous substances

## SECTION 14: Transport information

**General statements**  
**Transport by road/by rail (ADR/RID)**  
 14.1. UN number or ID number: Not applicable  
 14.2. UN proper shipping name: Not applicable  
 14.3. Transport hazard class(es): Not applicable  
 14.4. Packing group: Not applicable  
 14.5. Environmental hazards: Not applicable  
 Tunnel restriction code: Not applicable  
 Classification code: Not applicable  
 LQ: Not applicable  
 Transport category: Not applicable  
**Transport by sea (IMDG-code)**  
 14.1. UN number or ID number: Not applicable  
 14.2. UN proper shipping name: Not applicable  
 14.3. Transport hazard class(es): Not applicable  
 14.4. Packing group: Not applicable  
 14.5. Environmental hazards: Not applicable  
 Marine Pollutant: Not applicable  
 EmS: Not applicable  
**Transport by air (IATA)**  
 14.1. UN number or ID number: Not applicable  
 14.2. UN proper shipping name: Not applicable  
 14.3. Transport hazard class(es): Not applicable  
 14.4. Packing group: Not applicable  
 14.5. Environmental hazards: Not applicable  
**14.6. Special precautions for user**  
 Unless specified otherwise, general measures for safe transport must be followed.  
**14.7. Maritime transport in bulk according to IMO instruments**  
 Non-dangerous material according to Transport Regulations.

## SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
 Observe restrictions:  
 Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!  
 Regulation (EC) No 1907/2006, Annex XVII  
 Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate  
 Methylenediphenyl diisocyanate, modified  
 4,4'-methylenediphenyl diisocyanate  
 Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!  
 Comply with trade association/occupational health regulations.  
 Directive 2010/75/EU (VOC): ~ 33 g/l  
 Directive 2010/75/EU (VOC): 2,89 %  
 National requirements/regulations on safety and health protection must be applied when using work equipment.

**15.2 Chemical safety assessment**  
 A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections: 8  
 These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)  
 Revision date / version: 25.11.2024 / 0002  
 Replacing version dated / version: 13.09.2023 / 0001  
 Valid from: 25.11.2024  
 PDF print date: 28.11.2024  
 KNAPP PU+ KLEBER FASERVERSTÄRKT

**Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):**

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
STOT SE 3, H335	Classification according to calculation procedure.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Resp. Sens. 1, H334	Classification according to calculation procedure.
Skin Sens. 1, H317	Classification according to calculation procedure.
Carc. 2, H351	Classification according to calculation procedure.
STOT RE 2, H373	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.

- H373 May cause damage to organs through prolonged or repeated exposure by inhalation.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.

- Eye Irrit. — Eye irritation
- STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation
- Skin Irrit. — Skin irritation
- Resp. Sens. — Respiratory sensitization
- Skin Sens. — Skin sensitization
- Carc. — Carcinogenicity
- STOT RE — Specific target organ toxicity - repeated exposure
- Acute Tox. — Acute toxicity - inhalation
- Acute Tox. — Acute toxicity - oral
- Eye Dam. — Serious eye damage
- STOT SE — Specific target organ toxicity - single exposure - narcotic effects

**Key literature references and sources for data:**

- Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
- Guidelines for the preparation of safety data sheets as amended (ECHA).
- Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).
- Safety data sheets for the constituent substances.
- ECHA Homepage - Information about chemicals.
- GESTIS Substance Database (Germany).
- German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).
- EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.
- National Lists of Occupational Exposure Limits for each country as amended.
- Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

**Any abbreviations and acronyms used in this document:**

- acc., acc. to according, according to
- ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
- AOX Adsorbable organic halogen compounds
- approx. approximately
- Art., Art. no. Article number
- ASTM ASTM International (American Society for Testing and Materials)
- ATE Acute Toxicity Estimate
- BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany)
- BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
- BCF Bioconcentration factor
- BSEF The International Bromine Council
- CAS Chemical Abstracts Service
- CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
- CMR carcinogenic, mutagenic, reproductive toxic
- DMEL Derived Minimum Effect Level
- DNEL Derived No Effect Level
- DOC Dissolved organic carbon
- e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
- EbCx, EyCx, Eblx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
- EC European Community
- ECHA European Chemicals Agency
- ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
- EEC European Economic Community
- EINECS European Inventory of Existing Commercial Chemical Substances
- ELINCS European List of Notified Chemical Substances
- EN European Norms
- EPA United States Environmental Protection Agency (United States of America)
- ErCx, EpCx, Erlx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
- etc. et cetera

- EU European Union
- EVAL Ethylene-vinyl alcohol copolymer
- Fax Fax number
- gen. general
- GHS Globally Harmonized System of Classification and Labelling of Chemicals
- GWP Global warming potential
- Koc Adsorption coefficient of organic carbon in the soil
- Kow octanol-water partition coefficient
- IARC International Agency for Research on Cancer
- IATA International Air Transport Association
- IBC (Code) International Bulk Chemical (Code)
- IMDG-code International Maritime Code for Dangerous Goods
- incl. including, inclusive
- IUCLID International Uniform Chemical Information Database
- IUPAC International Union for Pure Applied Chemistry
- LC50 Lethal Concentration to 50 % of a test population
- LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
- Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
- Log Kow, Log Pow Logarithm of octanol-water partition coefficient
- LQ Limited Quantities
- MARPOL International Convention for the Prevention of Marine Pollution from Ships
- mg/kg bw mg/kg body weight
- mg/kg bw/d, mg/kg bw/day mg/kg body weight/day
- mg/kg dw mg/kg dry weight
- mg/kg wwt mg/kg wet weight
- n.a. not applicable
- n.av. not available
- n.c. not checked
- n.d.a. no data available
- NIOSH National Institute for Occupational Safety and Health (USA)
- NLP No-longer-Polymer
- NOEC, NOEL No Observed Effect Concentration/Level
- OECD Organisation for Economic Co-operation and Development
- org. organic
- OSHA Occupational Safety and Health Administration (USA)
- PBT persistent, bioaccumulative and toxic
- PE Polyethylene
- PNEC Predicted No Effect Concentration
- ppm parts per million
- PVC Polyvinylchloride
- REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
- REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
- RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
- SVHC Substances of Very High Concern
- Tel. Telephone
- TOC Total organic carbon
- UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
- VOC Volatile organic compounds
- vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:  
**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.